

# E-Z-Go RXV Utility Box Installation Instructions



1. Remove canopy top using 15mm tooling. If re-installing canopy, save hardware.
2. Remove front seat back cushion using Torx tooling; save hardware.
3. Remove access panel; save hardware.
4. Remove seat back supports using 15mm tooling; save hardware. Remove boots & discard.
5. Remove (2) bolts from bag well floor area using Torx tooling; save hardware.
6. Install new rear seat back support boots.
7. Install new rear seat back supports using existing hardware from step 3.
8. Install vertical support bracket into the bag well area reusing existing hardware from step 5. Attach horizontal box support to vertical support bracket using supplied hardware.
9. Install access cover removed in step 4.
10. If reinstalling top canopy, install top struts and canopy top removed in step 1.
11. Attach seat back to rear strut support using hardware from step 2.
12. Mount box on mounting brackets. Center the box. From underneath, mark the holes on the box through mounting brackets. Flip the box over, drill 3/8" holes at each of the marks. Use 10mm low profile truss head bolts to fasten box to mounting brackets. Use washers under brackets.
13. Install chain using 6mm x 25mm bolts through holes in box by tailgate.

## **Bill of Material**

- (2) Rear Seat Supports – Driver & Passenger
- (1) Vertical Support Bracket
- (1) Horizontal Box Support
- (2) Rear Seat Support Boots
- (1) Horizontal Alignment Bar
- (1) Box of Hardware